



# SATIN FINISH

Low Gloss Floor Finish

## DESCRIPTION

**Satin Finish** is a unique polymer system that provides a durable, matte finish for use in healthcare facilities where depth perception is a problem.

**Satin Finish's** unique polymer system is extremely durable extending the film's life, requiring less stripping and recoating. **Satin Finish** can be used on most types of resilient flooring such as linoleum, marmoleum, vinyl sheet and vinyl composite tile.

**Satin Finish's** user-friendly formula with excellent leveling and recoatability produce a clear non-yellowing film that can be repeatedly mopped with neutral cleaners like *NeutraMax* or *Orderly* - a neutral disinfectant used in healthcare facilities.

## DIRECTIONS

### **Preparation:**

Remove old finish with a quality stripper like *#1 Remover* as per label directions. When floor is clean and dry, **Satin Finish** can be applied in thin even coats allowing 20-30 minutes between coats. **Satin Finish** can be used without a sealer. However, on a porous floor, it is beneficial to apply 2 coats of a premium sealer like *Maxim Foundation*.

### **Application:**

On non-porous or sealed floors apply 2-3 thin coats of **Satin Finish** allowing 20-30 minutes drying time. Applying more coats will start to build the shine.

### **Maintenance:**

Dust mop with treated mop daily. Damp mop with a neutral detergent, like *NeutraMax* or *Orderly* for best results. To recoat traffic lanes when required, scrub with *MultiMax* using a red or blue pad and apply 1-2 fresh coats where required.

## PHYSICAL DATA

Features	Acrylic polymer system
Appearance	Milky-white emulsion
Coverage	2,500 to 3,500 sq.ft. per gallon when building film
Slip Resistance	Passes ASTM D2047
Total Solids	16.0 % (non-volatile) minimum

